

EU4400

High-density polyethylene (HDPE)



Description

EU4400 is a high-density polyethylene resin produced by Univation(Gas) Process, suitable for communication cable insulation. It provides high mechanical properties, environmental and thermal stress cracking resistance. In addition, EU4400 is designed for high-speed wire insulating extrusion process.

Characteristics

- Excellent processability
- Excellent heat-resistant stability
- High ESCR

Applications

- Solid insulation of communication wire
- Network & industrial ethernet data cable

Properties

Properties		Test Method		Values	Unit
Physical	Melt Flow Index (190°C, 2.16kg)	ASTM	D1238	0.75	g/10min
	Density	ASTM	D1505	0.945	g/cm ³
Mechanical	Tensile Stress (Yield)	ASTM	D638	240	kgf/cm ²
	Tensile Strain (Break)	ASTM	D638	> 500	%
	ESCR	ASTM	D1693	> 1,000	F50hr
Thermal	Oxidative Induction Time (200°C)	ASTM	D3895	> 50	min
Electrical	Dielectric Constant	ASTM	D150	< 2.3	-
	Dissipation Factor	ASTM	D150	0.0001	-
	Volume Resistivity	ASTM	D257	> 1 X 10 ¹⁶	Ω·cm
	Dielectric Strength	ASTM	D149	> 20	kV/mm

• NOTE : these are not to be construed as specifications

*DISCLAIMER : THIS DOCUMENT (INCLUDING ANY ENCLOSURES AND ATTACHEMENTS) HAS BEEN PREPARED FOR THE EXCLUSIVE USE AND BENEFIT OF THE ADDRESSEE(S) AND SOLELY FOR THE PURPOSE FOR WHICH IT IS PROVIDED. LOTTE CHEMICAL MAKES NO WARRANTY OR REPRESENTATION WHATSOEVER, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THIS DOCUMENT OR ANY INFORMATION HEREIN; AND LOTTE CHEMICAL ASSUMES NO LIABILITY WHATSOEVER WITHOUT LIMITATION WITH RESPECT TO ANY DAMAGES INCLUDING, BUT NOT LIMITED

