

PU4600

High-density polyethylene (HDPE)



Description

PU4600 is a high-density polyethylene resin produced by Univation(Gas) Process, suitable for Drip Irrigation Pipe which has high Melt-Strength and ESCR having excellent processability.

Characteristics

- High Melt-Strength
- Good processability, Good mechanical properties
- High ESCR

Applications

- Drip Irrigation Pipe
- Geo Sheet

Properties

	Properties	Test Method		Values	Nominal
Physical	Melt Flow Index (190°C, 2.16kg)	ASTM	D1238	0.19	g/10min
	Melt Flow Index (190°C, 21.6kg)	ASTM	D1238	20.0	g/10min
	Density	ASTM	D1505	0.939	g/cm ³
Mechanical	Tensile Stress (Yield)	ASTM	D638	190	kgf/cm ²
	Tensile Stress (Break)	ASTM	D638	300	kgf/cm ²
	Tensile Strain (Break)	ASTM	D638	> 700	%
	Flexural Modulus	ASTM	D790	6,500	kgf/cm ²
	Notched IZOD Impact Strength (23°C)	ASTM	D256	NB	kgf-cm/cm
	ESCR	ASTM	D1693	> 1,000	Fohr
Thermal	Vicat Softening Temperature	ASTM	D1525	115	°C
	Melting Temperature	ASTM	D3418	125	°C
	Oxidation Induction Time (200°C)	ISO/TR	10837	> 30	min

• NOTE : these are not to be construed as specifications

*DISCLAIMER : THIS DOCUMENT (INCLUDING ANY ENCLOSURES AND ATTACHEMENTS) HAS BEEN PREPARED FOR THE EXCLUSIVE USE AND BENEFIT OF THE ADDRESSEE(S) AND SOLELY FOR THE PURPOSE FOR WHICH IT IS PROVIDED. LOTTE CHEMICAL MAKES NO WARRANTY OR REPRESENTATION WHATSOEVER, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THIS DOCUMENT OR ANY INFORMATION HEREIN; AND LOTTE CHEMICAL ASSUMES NO LIABILITY WHATSOEVER WITHOUT LIMITATION WITH RESPECT TO ANY DAMAGES INCLUDING, BUT NOT LIMITED