

MF5000

High-density polyethylene (HDPE)



Description

MF5000 is a high-density polyethylene resin produced by Slurry(CSTR) Process, suitable for flat yarn / monofilament which has good stretching, spinning, high strength property and melting stability

Characteristics

- Good stretching and spinning
- High strength property and melting stability

Applications

- Monofilament for rope and net
- Flat yarn, stretched tape

Properties

	Properties	Test Method	Values	Nominal
Physical	Melt Flow Index (190°C, 2.16kg)	ASTM D1238	0.95	g/10min
	Density	ASTM D1505	0.956	g/cm ³
Mechanical	Flexural Modulus	ASTM D790	9,000	kgf/cm ²
	Tensile Stress (Yield)	ASTM D638	250	kgf/cm ²
	Tensile Strain (Break)		500	%
	Rockwell Hardness	ASTM D785	50	R

• NOTE : these are not to be construed as specifications

*DISCLAIMER : THIS DOCUMENT (INCLUDING ANY ENCLOSURES AND ATTACHEMENTS) HAS BEEN PREPARED FOR THE EXCLUSIVE USE AND BENEFIT OF THE ADDRESSEE(S) AND SOLELY FOR THE PURPOSE FOR WHICH IT IS PROVIDED. LOTTE CHEMICAL MAKES NO WARRANTY OR REPRESENTATION WHATSOEVER, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THIS DOCUMENT OR ANY INFORMATION HEREIN; AND LOTTE CHEMICAL ASSUMES NO LIABILITY WHATSOEVER WITHOUT LIMITATION WITH RESPECT TO ANY DAMAGES INCLUDING, BUT NOT LIMITED TO, DIRECT, INDIRECT, SPECIAL, CONSEQUENTIAL, OR PUNITIVE DAMAGES ARISING OUT OF, RESULTING FROM, OR ANY WAY CONNECTED TO ANY USE OF THIS DOCUMENT OR ANY INFORMATION HEREIN.