

# LVS430

## Ethylene vinyl acetate copolymer (EVA)



### General Information

LVS430 is an ethylene vinyl acetate resin produced in the tubular process, designed for foaming and sheet molding, and has excellent processability and mechanical properties.

### Key Features

- Excellent foaming properties and mechanical properties
- Vinyl Acetate Content 18%

### Applications

- Foam, Shoe soles, Injection/Sheet molding

### Properties

	Item	Measuring Method	대표치	Unit
Physical	Melt Flow Index (190°C, 2.16kg)	ASTM D1238	2.0	g/10min
	Density	ASTM D1505	0.940	g/cm <sup>3</sup>
	Vinyl Acetate Content	LC Method	18	wt%
Mechanical	Tensile Stress (Break)	ASTM D638	260	kgf/cm <sup>2</sup>
	Tensile Strain (Break)	ASTM D638	750	%
Thermal	Melting Point	LC Method	86	°C
	VICAT Softening Point	ASTM D1525	64	°C
Additional	Hardness (Shore A)	ASTM D2240	92	A Scale

• NOTE : Physical Properties : these are not to be construed as specifications

\* Disclaimer: All information in this document is for reference only and is not a final product specification. Before using our products, the customer must determine for himself the suitability, safety and legality of the intended use. We do not assume any liability or responsibility for the use of this document or the contents of this document, and we reserve the right to change the contents of this